

A 30 Micron Aluminium Foil Tape tested to BS476 part 6 and 7 standards meeting Class 1 and Class 0 Fire Regulations

This product has a pressure sensitive solvent acrylic adhesive protected with an easy release liner

UV, Water and Fire resistant it is ideal for sealing joints/seams against moisture and vapour

Also suitable for holding, splicing or masking applications requiring protection offered by foil backing

No Chlorine or Chlorine compounds or chlorides were used in the production process

### Uses:

Mirror backing, Insulation, Joint Sealing Foil, Fibre Glass Insulation. Wide width uses for decorating and fire-rating other insulation materials

Heat reflection and screening on electronic equipment. Sealing Cold Storage Insulation, packing refrigerated export containers

### Application:

Surfaces to be bonded must be clean, dry and free from dust

### Storage:

Normal room temperature

### Technical Data:

Width 600mm

Length 45m

Micron 30

Backing Thickness	30 Micron
Total Thickness	65 Micron
Peel Adhesion	20 N/25mm
Total Rolling Ball	20cm
Tensile Strength	37.5 N/25mm
Elongation	3.0%
Service Temperature	-30°C ~ +120°C
Applying Temperature	+10°C ~ +40°C

### Statement

Above information is given in good faith and for guidance only. Quoted values are based on average values determined by standard test measures and as such are not binding.

These should not be taken as maximum or minimum values for specific purposes.

Environmental conditions, application standards and technology changes can alter the properties of the materials with which our products are expected to perform.

The user shall be responsible for determining that the performance of the product is suitable for the application.

### European Headquarters

C.R. Laurence of Europe Ltd  
Charles Babbage Avenue, Kingsway Business Park  
Rochdale OL16 4NW  
Freephone: 00 800 0421 6144  
Freefax: 00 800 0262 3299  
Email: [crl@crlaurence.eu](mailto:crl@crlaurence.eu)  
Web: [www.crlaurence.eu](http://www.crlaurence.eu)