

# **CRL Oil Dynamic Hinges**For Glass Doors

Introducing CRL's new range of oil dynamic hinges for self-closing glass doors. The innovative hinges have adjustable closing speed and offer a great alternative to floor closers and patch fittings.



# **CRL Oil Dynamic Wall to Glass Hinge**

### Specification:

- Adjustable closing speed
- Swings in and out a full 90 degrees, with stops at 0°,+90°, and -90°
- Also available in no-hold open option
- 100kg max weight
- 1000mm max door width
- 8mm to 13.52mm glass

31M8010SN	Satin Nickel	Wall to Glass Hinge
31M8010SA	Satin Anodised	Wall to Glass Hinge
31M8010CH	Chrome	Wall to Glass Hinge
Than to alaborating		

#### NO HOLD OPEN OPTION

31M8210SN	Satin Nickel	Wall to Glass Hinge
31M8210SA	Satin Anodised	Wall to Glass Hinge
31M8210CH	Chrome	Wall to Glass Hinge

#### **CLAD OPTION**

31M8010CBS	Brushed Stainless	Wall to Glass Hinge
31M8010CPS	Polished Stainless	Wall to Glass Hinge

## FOR HIGH HUMIDITY RESISTANCE IN DAMP ENVIRONMENTS

31M8010BTSN	Satin Nickel	Wall to Glass Hinge
31M8010BTSA	Satin Anodised	Wall to Glass Hinge
31M8010BTCH	Chrome	Wall to Glass Hinge



# **CRL Oil Dynamic Offset Wall to Glass Hinge**

# Specification:

- Adjustable closing speed
- Swings in and out a full 90 degrees, with stops at 0°, +90°, and -90°
- Also available in no-hold open option
- 100kg max weight
- 1000mm max door width
- 8mm to 13.52mm glass

CAT. NO.	FINISH	DESCRIPTION
31M8011SN	Satin Nickel	Offset Wall to Glass Hinge
31M8011SA	Satin Anodised	Offset Wall to Glass Hinge
31M8011CH	Chrome	Offset Wall to Glass Hinge

# NO HOLD OPEN OPTION

31M8015BTCH

31M8211SN	Satin Nickel	Offset Wall to Glass Hinge
31M8211SA	Satin Anodised	Offset Wall to Glass Hinge
31M8211CH	Chrome	Offset Wall to Glass Hinge

## FOR HIGH HUMIDITY RESISTANCE IN DAMP ENVIRONMENTS

Satin Nickel	Offset Wall to Glass Hinge
Satin Anodised	Offset Wall to Glass Hinge
Chrome	Offset Wall to Glass Hinge
	Satin Anodised



# **CRL Oil Dynamic Glass to Glass Hinge**

# Specification:

- Adjustable closing speed
- Swings in and out a full 90 degrees, with stops at 0°, +90°, and –90°.
- Also available in no-hold open option
- 80kg max weight
- 1000mm max door width
- 8mm to 13.52mm glass

CAT. NO.	FINISH	DESCRIPTION	
31M8015SN	Satin Nickel	Glass to Glass Hinge	
31M8015SA	Satin Anodised	Glass to Glass Hinge	
31M8015CH	Chrome	Glass to Glass Hinge	
NO HOLD OPEN OPTION	ON		
31M8215SN	Satin Nickel	Glass to Glass Hinge	
31M8215SA	Satin Anodised	Glass to Glass Hinge	
31M8215CH	Chrome	Glass to Glass Hinge	
CLAD OPTION			
31M8015CBS	Brushed Stainless	Glass to Glass Hinge	
31M8015CPS	Polished Stainless	Glass to Glass Hinge	
FOR HIGH HUMIDITY	RESISTANCE IN DAM	P ENVIRONMENTS	
31M8015BTSN	Satin Nickel	Glass to Glass Hinge	
31M8015BTSA	Satin Anodised	Glass to Glass Hinge	

Glass to Glass Hinge



# **CRL Oil Dynamic Rebated Wall to Glass Hinge**

# Specification:

- Adjustable closing speed
- For use with rebated door frames
- Swings out 90 degrees
- Stops at 90 degrees
- Hold open
- 8 to 12mm glass
- 100kg max weight
- 1000mm max door width

CAT. NO.	FINISH	DESCRIPTION	
31M8060SN	Satin Nickel	Wall to Glass Hinge	
31M8060CH	Chrome	Wall to Glass Hinge	
NO HOLD OPEN OPTION			
31M8260SN	Satin Nickel	Wall to Glass Hinge	
31M8260CH	Chrome	Wall to Glass Hinge	



# **CRL Oil Dynamic Patch Fitting Door Hinge With Back Check**

The CRL Oil Dynamic Patch Fitting Door Hinge is an innovative patch fitting for installation on interior doors. The self-closing patch fitting is designed for installation without the need for a floor box and is extremely quick and easy to install on to any floor. The patch fittings do not require any additional floor or overhead closing devices, yet maintain the advantages of a closing system. The closing speed is adjustable.

## Specification:

- Closing speed can be adjusted
- Swings in and out a full 90 degrees, with stops at 0°, +90°, and -90°.
- Also available in no-hold open option
- 100kg max weight
- 1000mm max door width
- 8mm to 13.52mm glass
- Matching top patch fittings available

CAT. NO.	FINISH	DESCRIPTION
WITH BACK CHECK		
31M100E10		Body of patch closer, excludes cover
WITHOUT BACK CHECK		
		Body of patch closer,
31M100E10NB		excludes cover
NO HOLD OPEN OPTION		
31M100E10NH0		Body of patch closer,
		excludes cover
CLAD ODTIONS*		
CLAD OPTIONS*	5	0 /
31M100E10COVBS	Brushed Stainless	Cover for patch closer
31M100E10COVPS	Polished Stainless	Cover for patch closer
31M100E10COVSA	Satin Anodised	Cover for patch closer
TOP PATCH FITTING		
31M100E20		Matching top patch fitting

<sup>\*</sup>Clad options fit top and bottom patch fittings shown above and below.

# For more information, call Technical Sales on 00 800 0421 6144 or visit www.crlaurence.co.uk





# **Call FREE on 00 800 0421 6144** Fax FREE on 00 800 0262 3299

#### Manchester

Charles Babbage Avenue Kingsway Business Park, Rochdale, OL16 4NW, England Tel: +44 (0) 1706 863 600

Fax: +44 (0) 1706 869 860 www.crlaurence.co.uk



## Stuttgart

Boschstrasse 7 D-74360 Ilsfeld Germany

Tel: +49 (0) 7062 915 93 15 Fax: +49 (0) 7062 915 93 16 www.crlaurence.de



# Copenhagen

Stamholmen 70 Unit B, DK-2650 Hvidovre Denmark Tel: +45 36 72 09 00

Fax: +45 36 70 33 35 www.crlaurence.dk



# France

Boschstrasse 7 D-74360 Ilsfeld Germany

Tel: +49 (0) 7062 915 93 15 Fax: +49 (0) 7062 915 93 16

www.crlaurence.fr

# View Our Full Range of Architectural Railing Systems...

Our EUHR11 Architectural Balustrade and Railing Systems Catalogue

- Glass Railings/Balustrades
- TAPER-LOC® Railing System
- Swinging Gate System
- Post Railing Systems
- Welded Railing Systems
- Hand Railing Systems
- Aluminium Railing Systems
- Glass Walls/Windscreens
- Tools/Accessories

# You may also be interested in...

EUAH11 Architectural Hardware 'All Glass' Entrance Systems Catalogue

- Architectural Metals
- Door and Sidelite Bails
- Door Closers
- Centre Locks
- Glass Clamps
- Headers and Channels
- Ladder Pulls
- Locking Hardware
- Door Closers and Hinges
- Patch Hardware
- Pivot Door Systems
- Push/Pull Handles
- Sliding and Stacking Glass Door Systems
- Spider Fittings
- Standoff Systems

Catalogues are available to download or view online at crlaurence.co.uk or crlaurence.de

